

Models	15 EFI	20 EFI	30 EFI
Kilowatts	11.0	14.7	2.6
Max.RPM at Full Throttle	5700 - 6200	5700 - 6200	5000 - 6000
Cylinders	2 (in-line)	2 (in-line)	3 (in-line)
Smart Craft Compatible	N/A	N/A	N/A
Displacement	333 cc	333 cc	526 cc
Starting	Manual or electric	Manual or electric	Manual or electric
Gear Ratio	2.15:1	2.15:1	1.92:1
Gear Shift	F-N-R	F-N-R	F-N-R
Steering Midsection	Tiller or remote	Tiller or remote	Tiller or remote
Alternator System	12 amp (145 W)	12 amp (145 W)	15 amp (186 W)
Fuel System	EFI	EFI	EFI
Trim Positions	6 & SWD or EHT	6 & SWD or EHT	EHPT or GAT or MTT
Fuel Tank	12 L	12 L	25 L
Fuel Requirements	UL95R	UL95R	UL95R
Weight	45 kg	45 kg	71 kg
Available Boat Transom Heights	S - L	S - L	S - L
Counter Rotation	N/A	N/A	N/A

GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

STEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section
EHPS: Electric Hydraulic Power Steering
BTO: Big Tiller Optional • **RO:** Remote optional

ALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional
OPT: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging
ML: ML Models only

FUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection
DFI: Direct Fuel Injection • **CARB:** through carburetor

TRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt
SWD: Shallow Water drive

FUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional

AVAILABLE BOAT

TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)

COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)

