

Models	8	9.9
Kilowatts	5.9	7.3
Max.RPM at Full Throttle	5000 - 6000	5000 - 6000
Cylinders	2 (in-line)	2 (in-line)
Smart Craft Compatible	N/A	N/A
Displacement	208 cc	208 cc
Starting	Manual or electric	Manual or electric
Gear Ratio	2.08:1	2.08:1
Gear Shift	F-N-R	F-N-R
Steering Midsection	Tiller or remote	Tiller or remote
Alternator System	6 amp (76 W) ESM	6 amp (76 W) ESM
Fuel System	CARB	CARB
Trim Positions	6 & SWD	6 & SWD or EHT
Fuel Tank	12 L	12 L
Fuel Requirements	UL95R	UL95R
Weight	38 kg	38 kg
Available Boat Transom Heights	S - L	S - L
Counter Rotation	N/A	N/A

GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

STEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section
EHPS: Electric Hydraulic Power Steering
BTO: Big Tiller Optional • **RO:** Remote optional

ALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional
OPT: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging
ML: ML Models only

FUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection
DFI: Direct Fuel Injection • **CARB:** through carburetor

TRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt
SWD: Shallow Water drive

FUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional

AVAILABLE BOAT

TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)

COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)

